

Tel: +27 12 803 8595
Fax: +27 12 803 8462
Customer care line: 086 1554 321
e-mail: timberlife@icon.co.za
Website: www.timberlife.co.za

TIMBERLIFE (PTY) LTD
REG No 2000/017132/07

PO Box 73117, Lynnwood Ridge, 0040
31 Axle Street
Silverton Ext 52
Pretoria, South Africa



PRODUCT DATA SHEET

Furno-Coat

Product Name: FURNO-COAT

Product Type: HIGH OIL CONTENT, SINGLE COAT, WOOD STABILIZING & WATER REPELLENT SEALER FOR FURNITURE AND JOINERY

Description: **Furno-Coat** is a solvent free, high oil content (> 97% v/v), wood stabilizing and water repellent wood sealer for aesthetic and protective treatment of uncoated indoor and outdoor timbers in a single coat application. It is ideal for use on timbers such as wooden furniture, joinery, cladding, flooring, etc. where a natural clear or coloured matt to low sheen finish is preferred.

Furno-Coat has been specially formulated for the addition of specialized wood colouring "**Solv-Tints**" pigment dispersions that are based on high-quality, UV resistant transparent iron oxide pigments to provide a range of "washed" colour effects in a single coat application.

Furno-Coat has a high content of urethane alkyds and natural drying oils that provides a high degree of wood stabilization and water repellency to the sealed wood surface. It deeply penetrates, nourishes and seals the wood from the inside out and dries to a natural, satin-like matt finish. **Furno-Coat** also contains UV absorbing and light stabilizing additives to enhance its performance against sunlight degradation when used on outdoor timbers.

Active Ingredients: Urethane alkyds and drying oils with UV absorbers and light stabilizers

Physical

Characteristics:	Appearance	-	Translucent, deep brown liquid
	Solubility	-	Oil borne
	Density @ 20°C	-	± 0,96 kg/l

Use Restriction: Not recommended for use on previously coated timber surfaces. Remove old coatings and thoroughly sand surface before application of **Furno-Coat**.

Application: Use a clean, soft cloth, sponge or soft bristle brush dipped in **Furno-Coat** and apply in light, short strokes, ensuring thorough and even distribution of the oil. Leave the oil on for at least 15 to 20 minutes (but not more than 30 minutes) to allow for absorption into the wood. Wipe off any excess liquid, leaving a natural smooth finish. Simply reapply further coats as and when desired.
Touch dry within 40 to 60 minutes and fully cured within 24 to 36 hours.
Timber can be left as is or alternatively, any of TimberLife's clear solvent-based or water-based wood sealers/coatings can be applied as a final finish/topcoat.

Application Rate: 20m² - 40m² per l per application, depending on condition of the surface.

Dilution Rates: Ready for use. DO NOT DILUTE.

Storage: Storage temperatures should not exceed 40°C. Keep container tightly sealed.

Packaging: 1l, 5l, 25l and 200l containers.

Caution: The product is combustible. Avoid open flames. Used cloths and sponges may ignite spontaneously – Dispose of in a safe manner or completely submerge in water after use.